



TECHNICAL DATA SHEET

PROFESSIONAL SCREENING

rev. 05/2024

PRODUCT IDENTIFICATION	SUNOX 180
USE	ROLL UP SCREEN
MANUFACTURE	WOVEN
STIFFNESS	STIFF
AVAILABLE COLOURS	CHARCOAL
COMPOSITION	FIBERGLASS: 38% PVC: 62%
MESH	18X16
WEIGHT	109 gr/mq +/- 2%
THICKNESS	mm 0,30 +/- 0,04
OPENNESS (% SUNLIGHT)	63%
ULTIMATE STRENGTH WARP	N/50mm 740
ULTIMATE STRENGTH FILL	N/50mm 590
PACKING	Cardboard tubes
WIDTHS	cm 160/180/260
ROLL LENGTH	ml 90
WELDING	HEAT-HIGH FREQUENCY-ULTRASONIC
HEAT RESISTANCE	Da -35°C a +80°C
FLAME RESISTANCE	CLASS 2 SELF-EXTINGUISHING
CLEANING	WATER AND SOAP
SUNOX IS NOT A PROTECTION DEVICE AGAINST SARS COV-2	
NOMINAL DATA	

T.I.E. TESSITURA INDUSTRIALE EUROPEA S.P.A.
LOCALITÀ PETRONA - 50038 SCARPERIA - FI - ITALIA
TEL. 055.8494588 - FAX 055.8455255 - E-MAIL: TIE@RETTIE.COM
COD. FISC. 04747410480 - P. IVA IT 04747410480 - REA N. 477486
R.I. FIRENZE - CAPITALE SOCIALE EURO 1.500.000,00